




PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>H04S 1/00</b>	<b>A1</b>	(11) International Publication Number: <b>WO 98/36614</b> (43) International Publication Date: 20 August 1998 (20.08.98)
(21) International Application Number: PCT/IB98/00073 (22) International Filing Date: 19 January 1998 (19.01.98) (30) Priority Data: 08/800,636                      14 February 1997 (14.02.97)                      US (71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). (71) Applicant (for SE only): PHILIPS NORDEN AB [SE/SE]; Kottbygatan 7, Kista, S-164 85 Stockholm (SE). (72) Inventor: SCHIOTT, Wayne, M.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). (74) Agent: GROENENDAAL, Antonius, W., M.; Internationaal Octrooibureau B.V., P.O. Box 220, NL-5600 AE Eindhoven (NL).		(81) Designated States: JP, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report.          Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: CREATING AN EXPANDED STEREO IMAGE USING PHASE SHIFTING CIRCUITRY



## (57) Abstract

In portable stereo radio receivers and television receivers, the loudspeakers therein may be separated only by a limited amount. This severely restricts the stereo image created by the loudspeakers. A circuit arrangement for creating an expanded stereo image may be incorporated in such receivers. This circuit arrangement first forms a combined monaural signal (at 10) and a differential signal (at 12) from the two stereo signals ( $L_{in}$ ,  $R_{in}$ ). The differential signal is then subjected to a phase shift (at 14). The phase-shifted differential signal is then matrixed (at 16, 18) with the combined monaural signal to form output stereo signals ( $L_{out}$ ,  $R_{out}$ ). When reproduced through stereo loudspeakers, the stereo image appears to be greatly expanded, beyond the limited placement of the loudspeakers.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## Creating an expanded stereo image using phase shifting circuitry

### Background of the invention

### Field of The Invention

The subject invention relates to a signal processing circuit for enhancing a stereo image that corresponds to a stereo audio signal.

### 5 Description of The Related Art

In conventional stereo systems, the amplifying circuits amplify the left and right channel signals and pass these amplified signals to a left and right channel loudspeakers. This is done in an attempt to simulate the experience of a live performance in which the reproduced sounds emanate from different locations. Since the advent of stereo systems, there has been  
10 continual development of systems which more closely simulate this experience of a live performance. For example, in the early to mid 1970's, four-channel stereo systems were developed which included two front left and right channel loudspeakers and two rear left and right channel speakers. These systems attempted to recapture the information contained in signals reflected from the back of a room in which a live performance was being held. More  
15 recently, surround sound systems are currently on the market which, in effect, seek to accomplish the same effect.

A drawback of these systems is that there are four or more channels of signals being generated and a person must first purchase the additional loudspeakers and then solve the problem of locating the multiple loudspeakers for the system.

20 As an alternative to such a system, U.S. Patent 4,748,669 to Klayman discloses a stereo enhancement system which simulates this wide dispersal of sound while only using the two stereo loudspeakers. This system, commonly known as the Sound Retrieval System, uses dynamic equalizers, which boost the signal level of quieter components in the audio spectrum relative to louder components, a spectrum analyzer and a feedback and reverberation control  
25 circuit to achieve the desired effect. However, as should be apparent, this system is relatively complex and costly to implement.

### Summary of the invention

It is an object of the present invention to provide a circuit arrangement for enhancing the imaging of a stereo signal such that it seems much larger than the actual spacing between the stereo loudspeakers.

It is a further object of the invention to provide such a circuit arrangement that is  
5 relatively simple and inexpensive to implement.

The above objects are achieved in a circuit arrangement for creating an expanded stereo image in a stereo signal, comprising a first input and a second input for receiving, respectively, a left channel signal and a right channel signal of an input stereo signal; first combining means coupled to the first and second inputs for additively combining the left and  
10 right channel signals thereby forming a sum signal; first difference forming means also coupled to the first and second inputs for forming a difference between the left and right channel signals, thereby forming a difference signal; phase shifting means having an input for receiving said difference signal; second difference forming means having a first input for receiving said sum signal and a second input coupled to an output of said phase shifting means, said second  
15 difference forming means forming a left channel output signal; and second summing means having a first input for receiving said sum signal and a second input coupled to the output of said phase shifting means, said second summing means forming a right channel output signal.

Applicant has found that in small portable stereo receivers and in television receivers, the spacing between the stereo loudspeakers is limited. When the circuit arrangement  
20 of the subject invention is incorporated in such receivers, the stereo image is greatly expanded, much beyond the limited placement of the stereo loudspeakers.

#### Brief description of the drawings

With the above and additional objects and advantages in mind as will hereinafter appear, the invention will be described with reference to the accompanying drawings, in which:

25 Fig. 1 is a block diagram of a circuit arrangement for a first embodiment of the invention;

Fig. 2 is a block diagram of a modified circuit arrangement for a second embodiment of the invention;

Fig. 3 shows a plot of the response curves of the left output signal and the left  
30 crosstalk signal for the circuit arrangement of Fig. 2;

Fig. 4 shows a plot of the response curve of a phase shifter arrangement in the circuit arrangement of Fig. 2;

Fig. 5 shows a plot of response curves for the circuit arrangement of Fig. 2; and

Fig. 6 is a schematic diagram of the circuit arrangement for the second embodiment of the invention of Fig. 2.

#### Description of the preferred embodiments

5 Fig. 1 shows a basic block diagram of a circuit arrangement forming a first embodiment of the invention. A left channel input signal is applied to an input LIN of the circuit arrangement and then to a first input of a first summing circuit 10. A right channel input signal is applied to an input RIN of the circuit arrangement and then to a second input of the first summing circuit 10. Similarly, the left and right channel input signals are applied to first and  
10 second inputs, respectively, of a first difference circuit 12. An output from the first difference circuit 12 is applied to a phase shifter 14. An output from the first summing circuit 10 is connected to first inputs of a second difference circuit 16 and a second summing circuit 18, respectively, while an output from the phase shifter 14 is connected to second inputs of the second difference circuit 16 and the second summing circuit 18, respectively. The output LOUT  
15 of the second difference circuit 16 supplies the left channel output signal, while the output ROUT of the second summing circuit 18 supplies the right channel output signal.

The first summing circuit 10 is used to generate a monaural signal (L+R) and the first difference circuit 12 is used to generate a differential signal (L-R). This is done to prevent amplitude and phase fluctuations in the left and right channel output signals when the circuit  
20 arrangement is driven by an (L+R) signal.

The circuit arrangement as shown in Fig. 1 does indeed produce the desired expansion of the stereo image when the gains in the summing and difference circuits are not balanced.

Fig. 2 shows a basic block diagram of a working embodiment of the invention. In  
25 particular, the left channel input signal is applied to an input LIN of the circuit arrangement, while the right channel input signal is applied to an input RIN. The input LIN is connected to the first inputs of a first matrix circuit 20 and a second matrix circuit 22, respectively, and the input RIN is connected to the second input of the first and second matrix circuits 20 and 22, respectively. The first matrix circuit 20 forms the sum signal (L+R) and has a gain of 0 dB. The  
30 second matrix circuit 22 forms the difference signal (L-R) and has a gain of 14 dB. the output from the second matrix circuit 22 is applied to a phase shifter arrangement 24. The output from the first matrix circuit 20 is applied to the first inputs of a third matrix circuit 26 and a fourth matrix circuit 28, while the output from the phase shifter arrangement 24 is applied to the second

inputs of the third and fourth matrix circuits 26 and 28. The third matrix circuit 26, which supplies the left channel output signal to the output LOOUT of the circuit arrangement, provides a 0 dB gain for the output from the first matrix circuit 20, and a 6 dB gain for the output from the phase shifter arrangement 24. The fourth matrix circuit 28, which supplies the right channel output signal to the output ROOUT of the circuit arrangement, provides a 0 dB gain for the output signal from the first matrix circuit 20, and a 6 dB gain for the output signal from the phase shifter arrangement 24.

The phase shifter arrangement 24 is formed by the series arrangement of two all pass phase shifters 30 and 32, each providing a gain of -6 dB. As such, the net gain for the (L+R) signal is 0 dB, while the net gain for the (L-R) signal is 8 dB, such that in certain areas of the audio frequency range, the differential between the desired left or right signal and the corresponding right or left cross-talk signal is 7-8 dB. This is shown in the plots A and B of Fig. 3, in which the responses of the LOOUT signal and the ROOUT cross-talk signal, respectively, are shown with respect to frequency. Fig. 3 further shows plots C and D of the phase of the LOOUT signal and the ROOUT crosstalk signal with respect to frequency.

Fig. 4 shows a plot of the amplitude response/gain E (in dB) with respect to frequency, and the combined phase F (in degrees) with respect to frequency of the phase shifter arrangement 24. It should be noted that the amplitude response/gain produces a flat line at -12 dB, while the phase varies from approximately -60 degrees to -700 degrees.

Fig. 5 shows a plot of the overall gain (in dB) and phase (in degrees) of the circuit arrangement. In Fig. 5, line G represents the (L+R) gain, line H represents the (L+R) phase response, line I represents the amplitude response of a single channel (L or R), and line J represents the phase response of a single channel (L or R).

Fig. 6 is a schematic diagram of circuit arrangement for a practical embodiment of the invention. In particular, the left input LIN is connected to ground through a resistor R1 and, through the series arrangement of a first capacitor C1, a second capacitor C2 and a resistor R2 to the inverting input of a differential amplifier A1. Similarly, the right input RIN is connected to ground through a resistor R1 and, through the series arrangement of a capacitor C3 and a resistor R4, to the inverting input of summing amplifier A2. The junction between capacitors C1 and C2 is also connected to the inverting input of summing amplifier A2 through a resistor R5, while the junction between capacitor C3 and resistor R4 is connected to the non-inverting input of differential amplifier A1 through the series combination of capacitor C4 and resistor R6. The inverting input of summing amplifier A2 is connected to its output via a resistor R7. Arranged as

such, differential amplifier A1 forms the matrix circuit 22 while summing amplifier A2 forms the matrix circuit 20.

The inverting input of differential amplifier A1 is connected to its output through a resistor R8 which is then connected, on the one hand, through a resistor R9, to the non-inverting input of differential amplifier A3, and on the other hand, through the series combination of a resistor R10 and a capacitor C5, to the inverting input of differential amplifier A3. The non-inverting input of differential amplifier A1 is also connected to ground through resistor R11, as is the non-inverting input of differential amplifier A3 connected to ground through resistor R12. The junction between resistor R10 and capacitor C5 is connected to the output of differential amplifier A3 via a capacitor C6, while the inverting input of differential amplifier A3 is connected to its output via a resistor R13.

The output of differential amplifier A3 is connected, on the one hand, through the series arrangement of a resistor R14 and a capacitor C7, to the inverting input of differential amplifier A4, and, on the other hand, through a resistor R15, to the non-inverting input of differential amplifier A4. The non-inverting input of differential amplifier A4 is connected to ground via resistor R16. The junction between resistor R14 and capacitor C7 is connected to the output of differential amplifier A4 via a capacitor C8, while the inverting input of differential amplifier A4 is connected to its output via a resistor R17. Differential amplifiers A3 and A4 thus form phase shifters 30 and 32 of the phase shifter arrangement 24.

The output of differential amplifier A4 is connected to the non-inverting input of differential amplifier A5, while the output of differential amplifier A2 is connected to the inverting input of differential amplifier A5 via a resistor R18. A resistor R19 connects the inverting input of differential amplifier A5 with its output which is, in turn, connected, through a series arrangement of a capacitor C9 and a resistor R20, to ground, the junction between the capacitor C9 and resistor R20 being connected to the left output LOUT. As such, differential amplifier A5 forms the matrix circuit 26.

The output of differential amplifier A2 is connected to the inverting input of differential amplifier A6 via a resistor R21, while the output of differential amplifier A4 is connected to this inverting input via a resistor R22. The non-inverting inputs of differential amplifiers A2 and A6 are connected to ground. A resistor R23 connects the non-inverting input of differential amplifier A6 to its output which is, in turn, connected, through the series combination of a capacitor C10 and a resistor R24, to ground, the junction between capacitor

C10 and resistor R24 being connected to the right output ROUT. As such, differential amplifier A6 forms the matrix circuit 28.

In an exemplary embodiment, the values of the above components are as follows:

5	RESISTORS	
	R1, R3, R20, R24	100 K $\Omega$
	R2, R6, R7, R18, R19, R22	10 K $\Omega$
	R4, R5, R21, R23	20 K $\Omega$
	R8, R11	27 K $\Omega$
10	R9, R12, R15, R16	47 K $\Omega$
	R10, R14	8.2 K $\Omega$
	R13, R17	33 K $\Omega$

	CAPACITORS	
15	C1, C3, C9, C10	5 $\mu$ F
	C2, C4	0.1 $\mu$ F
	C5, C6	47 nF
	C7, C8	6.8 nF

The differential amplifiers A1-A6 are each type LF347.

20 Numerous alterations and modifications of the structure herein disclosed will present themselves to those skilled in the art. However, it is to be understood that the above described embodiment is for purposes of illustration only and not to be construed as a limitation of the invention. All such modifications which do not depart from the spirit of the invention are intended to be included within the scope of the appended claims.



## CLAIMS

1. A circuit arrangement for creating an expanded stereo image in a stereo signal, comprising:
  - a first input and a second input for receiving, respectively, a left channel signal and a right channel signal of an input stereo signal;
  - 5 first combining means coupled to the first and second inputs for additively combining the left and right channel signals thereby forming a sum signal;
  - first difference forming means also coupled to the first and second inputs for forming a difference between the left and right channel signals, thereby forming a difference signal;
  - 10 phase shifting means having an input for receiving said difference signal;
  - second difference forming means having a first input for receiving said sum signal and a second input coupled to an output of said phase shifting means, said second difference forming means forming a left channel output signal; and
  - second summing means having a first input for receiving said sum signal and a second input coupled to the output of said phase shifting means, said second summing means forming a right channel output signal.
2. A circuit arrangement as claimed in claim 1, wherein said first and second combining means each comprises a matrix circuit.
3. A circuit arrangement as claimed in claim 2, wherein said first and second difference forming means each comprises a matrix circuit.
- 20 4. A circuit arrangement as claimed in claim 3, wherein said first combining means has a gain of 0 dB; said second combining means has a gain of 0 dB for the signal from the first combining means, and a gain of 6 dB for the signal from the phase shifting means; said first difference forming means has a gain of 14 dB; said second difference forming means has a gain of 0 dB for the signal from the first combining means, and a gain of 6 dB for the signal from the phase shifting means; and the phase shifting means has a gain of -12 dB.

5. A circuit arrangement as claimed in claim 1, wherein said phase shifting means comprises a series arrangement of two phase shifters, each of said phase shifters being all-pass (0E - 360E) phase shifting networks.

6. A circuit arrangement as claimed in claim 4, wherein said phase shifting means  
5 comprises a series arrangement of two phase shifters, each of said phase shifters being an all-pass (0E - 360E) phase shifting network having a gain of -6 dB.

1/5




FIG. 1




FIG. 2

2/5




FIG. 3

3/5




FIG. 4

4/5




FIG. 5

5/5




FIG. 6

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 98/00073

<b>A. CLASSIFICATION OF SUBJECT MATTER</b>		
<b>IPC6: H04S 1/00</b> According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b>		
Minimum documentation searched (classification system followed by classification symbols)		
<b>IPC6: H04R, H04S</b>		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
<b>SE,DK,FI,NO classes as above</b>		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
<b>EPODOC</b>		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4451927 A (D.L. HERSHBERGER), 29 May 1984 (29.05.84)  --	1-3
A	US 4349698 A (M. IWAHARA), 14 Sept 1982 (14.09.82)  --	
A	US 4748669 A (A.I. KLAYMAN), 31 May 1988 (31.05.88)  --	
A	US 4841572 A (A.I. KLAYMAN), 20 June 1989 (20.06.89)  -- -----	
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input checked="" type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "I" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search		Date of mailing of the international search report
12 June 1998		24-06-1998
Name and mailing address of the ISA/ Swedish Patent Office Box 5055, S-102 42 STOCKHOLM Facsimile No. +46 8 666 02 86		Authorized officer  Leif Vingård Telephone No. +46 8 782 25 00



# INTERNATIONAL SEARCH REPORT

Information on patent family members

29/04/98

International application No.

PCT/IB 98/00073

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
US	4451927	A	29/05/84	NONE		
US	4349698	A	14/09/82	JP	1254855 C	12/03/85
				JP	56001698 A	09/01/81
				JP	59031279 B	01/08/84
US	4748669	A	31/05/88	AU	587529 B	17/08/89
				AU	591609 B	07/12/89
				AU	597848 B	07/06/90
				AU	2205288 A	08/12/88
				AU	2205388 A	08/12/88
				AU	6934187 A	20/10/87
				CA	1284297 A	21/05/91
				DE	3752025 D,T	12/06/97
				DE	3752034 D,T	30/10/97
				DE	3752052 D,T	07/08/97
				DE	3784423 A,T	08/04/93
				EP	0262160 A,B	06/04/88
				SE	0262160 T3	
				EP	0476790 A,B	25/03/92
				SE	0476790 T3	
				EP	0478096 A,B	01/04/92
				SE	0478096 T3	
				EP	0479395 A,B	08/04/92
				SE	0479395 T3	
				EP	0748143 A	11/12/96
				HK	75293 A	06/08/93
				JP	2528154 B	28/08/96
				JP	2609065 B	14/05/97
				JP	7007798 A	10/01/95
				JP	7007799 A	10/01/95
				JP	63502945 T	27/10/88
				WO	8706090 A	08/10/87
US	4841572	A	20/06/89	CA	1299111 A	21/04/92
				KR	9402166 B	18/03/94
				WO	9011670 A	04/10/90

**This Page Blank (uspto)**